



2 t / hr Steam - Blow Off Silencer



30t/hr steam inline silencer



blow off silencer for natural gas



60 t/hr blow off silencer during lorry loading



# References Silencer



190t/hr steam blow off silencer - divided for transport



pressure vessel silencer. resonance / absorption type for roots blower

below: transport to site



below: damp tube



Absorption silencer after HRSG package



start up steam silencer with insertion loss of 60 dB

below: safety valve blow off silencer





12 t / hr Steam -  
Blow Off Silencer



30t/hr Blow Off Silencer

SS - Vent Silencer for 5.000 Nm<sup>3</sup>/hr of O<sub>2</sub>



above: 50 t/hr Steam- Blow Off Silencer



Preassembled Intake Silencer splitters for concrete-  
stack; 14.000 Nm<sup>3</sup>/hr.



2 stage Vent Silencer for Insertion Loss of > 60 dB



above: 18t/hr Blow Off Silencer for 500 °C

left: Waste Gas Silencer 5.000 Nm<sup>3</sup>/hr  
Insertion Loss 50 dB



# NOISEPROTECTION



# NOISEPROTECTION



Silencer with pressure expansion stages for venting of high temperature steam. Seeworthy packaging for transport to Thailand.



35 t/hr, 520°C Steam - Blow Off Silencer



SS-Inline Silencer for 4bar O<sub>2</sub>



Air Blower Bypassilencer 20.000Nm<sup>3</sup>/hr



Silencer for venting of technical gases as air, Nitrogen or Oxygen, taking special materials under consideration.



Spezial perforated expansion stages for max. loss of noise



15 t/hr Blow Off - Silencer



Stainless Steel Silencer for venting of pure oxygen with special mineral wool and inside treatment



Silencer upstream ventilator, designed for +/- 9.500 Pa. Stiffeners acc. to stacical analysis



Waste Gas Silencer with 3 nozzles and demountable exhaust hood.

Diameter: 1100mm  
Length: 5500mm  
Weight: 1400kg



## w&p NOISEPROTECTION GmbH

Enterbichl 1a

D - 82223 Seefeld - Hechendorf

Germany

Tel.: + 49 - 8152 - 399768

Fax.: +49 - 8152 - 969233

e - mail: [info@noiseprotection.de](mailto:info@noiseprotection.de)

<http://www.noiseprotection.de>